

msttcorefonts on RHEL6 / Centos 6 / SL6

Готовый rpm-пакет находится [здесь](#)

Источник <http://oimon.wordpress.com/2011/09/05/msttcorefonts-on-rhel6-centos-6-sl6/>

msttcorefonts is a way of obtaining the Microsoft TrueType fonts on Linux. However, version 6 release of Red Hat Enterprise Linux no longer includes a pre-requisite of msttcorefonts package, namely chkfontpath, which in turn, relies on the font server package xfs.

The latest version of msttcorefonts at sourceforge doesn't cater for this, so in the meantime we can patch the spec file and build it ourselves.

- 1) Download the spec file from <http://corefonts.sourceforge.net/msttcorefonts-2.0-1.spec>
- 2) Patch the spec file. Create a file called msttcorefonts.rhel6.patch, containing the following:

```
--- msttcorefonts-2.0-1.spec      2011-09-05 11:09:57.206756336 +0100
+++ msttcorefonts-2.0-1.1.spec   2011-09-05 11:23:56.925761649 +0100
@@ -19,8 +19,8 @@
 BuildPrereq: %{ttmkfdir}
 BuildPrereq: wget
 BuildPrereq: cabextract
-Prereq: /usr/sbin/chkfontpath
-Packager: Noa Resare <noa@resare.com>
+#Prereq: /usr/sbin/chkfontpath
+#Packager: Noa Resare <noa@resare.com>

%description
The TrueType core fonts for the web that was once available from
@@ -152,7 +152,7 @@
%post
if test $1 -eq 1
then
- /usr/sbin/chkfontpath --add %{fontdir}
+ ln -s /usr/share/fonts/msttcorefonts/ /etc/X11/fontpath.d/msttcorefonts
fi
# something has probably changed, update the font-config cache
if test -x /usr/bin/fontconfig
@@ -163,7 +163,7 @@
%preun
if test $1 -eq 0
then
- /usr/sbin/chkfontpath --remove %{fontdir}
+ /bin/rm -f /etc/X11/fontpath.d/msttcorefonts
fi
```

%files

3) Patch the spec file by running the following command in the same directory as the .spec file and the .patch
file{{:lcn:msttcorefonts-2.0-1.noarch.rpm|}}

```
patch < msttcorefonts.rhel6.patch
```

Visually inspect the resulting spec file to verify that it no longer requires chkfontpath.

4) Rebuild the rpm package using the new spec file
rpmbuild -bb msttcorefonts-2.0-1.spec

5) Finally, copy the resulting RPM to your local repository, or install locally with
yum localinstall msttcorefonts-2.0-1.noarch.rpm

From:
<https://theory.npi.msu.su/dokuwiki/> - **THEORY**

Permanent link:
<https://theory.npi.msu.su/dokuwiki/doku.php/lcn/msfonts>

Last update: **02/12/2012 14:20**

